

SAFETY DATA SHEET

FCAT# 6001616

Honeywell
Fluka™

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

SECTION 1. IDENTIFICATION

Product name : Sulfuric acid solution

Number : 000000021291

Product Use Description : Laboratory chemicals

Manufacturer or supplier's details : Honeywell International Inc.
1953 South Harvey Street
Muskegon, MI 49442



For more information call : 1-800-368-0050
+1-231-726-3171

(Monday-Friday, 9:00am-5:00pm)

In case of emergency call : **Medical: 1-800-498-5701 or +1-303-389-1414**
: **Transportation (CHEMTREC): 1-800-424-9300 or +1-703-527-3887**

:
: (24 hours/day, 7 days/week)

SECTION 2. HAZARDS IDENTIFICATION

Emergency Overview

Form : liquid

Color : colourless

Odor : odourless

Classification of the substance or mixture

Classification of the substance or mixture : Corrosive to metals, Category 1
Skin corrosion, Category 1B
Serious eye damage, Category 1

GHS Label elements, including precautionary statements

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

Symbol(s)

:



Signal word

: Danger

Hazard statements

: May be corrosive to metals.
Causes severe skin burns and eye damage.

Precautionary statements

: **Prevention:**
Keep only in original container.
Wash skin thoroughly after handling.
Wear protective gloves/protective clothing/eye protection/face protection.**Response:**

IF SWALLOWED: rinse mouth. Do NOT induce vomiting.

IF ON SKIN (or hair): Remove/ Take off immediately all contaminated clothing. Rinse skin with water/ shower.

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Immediately call a POISON CENTER/doctor.

Wash contaminated clothing before reuse.

Absorb spillage to prevent material damage.

Storage:

Store locked up.

Store in corrosive resistant container with a resistant inner liner.

Disposal:

Dispose of contents/ container to an approved waste disposal plant.

Carcinogenicity

| | | |
|--------|--|-----------|
| NTP: | Sulfuric Acid Known To Be Human Carcinogen. | 7664-93-9 |
| IARC: | Sulfuric Acid Group 1: Carcinogenic to humans | 7664-93-9 |
| ACGIH: | Sulfuric Acid | 7664-93-9 |

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

A2: Suspected human carcinogen

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTSFormula : H₂SO₄

Chemical nature : Mixture

| Chemical name | CAS-No. | Concentration |
|---------------|-----------|----------------------|
| Water | 7732-18-5 | >=90.00 - <=100.00 % |
| Sulfuric Acid | 7664-93-9 | >=5.00 - <10.00 % |

SECTION 4. FIRST AID MEASURES

- General advice : First aider needs to protect himself. Move out of dangerous area. Immediately take off contaminated clothing and rinse body with plenty of water.
- Inhalation : Remove to fresh air. If breathing is difficult, give oxygen. Use oxygen as required, provided a qualified operator is present. Call a physician immediately.
- Skin contact : Wash off immediately with plenty of water for at least 15 minutes. Take off contaminated clothing and shoes immediately. Immediate medical treatment is necessary as untreated wounds from corrosion of the skin heal slowly and with difficulty. Call a physician immediately.
- Eye contact : Protect unharmed eye. Irrigate eyes for at least 15 minutes with copious quantities of water, keeping eyelids apart and away from eyeballs during irrigation. Small amounts splashed into eyes can cause irreversible tissue damage and blindness. Call a physician immediately.
- Ingestion : Clean mouth with water and drink afterwards plenty of water. Magnesium hydroxide (milk of Magnesia) as an antacid may be given. Do NOT induce vomiting. Call a physician immediately.

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Foam
Carbon dioxide (CO₂)
Dry powder
- Unsuitable extinguishing media : Water
Do NOT use water jet.
Contact with a relatively small quantity of water creates violent reaction generating much heat and spattering of hot acid
- Specific hazards during firefighting : Contact with combustible material may cause fire.
In case of fire hazardous decomposition products may be produced such as:
Sulphur oxides
- Special protective equipment for firefighters : Wear self-contained breathing apparatus and protective suit.
No unprotected exposed skin areas.
- Further information : The product itself does not burn.
Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Evacuate personnel to safe areas.
Wear personal protective equipment. Unprotected persons must be kept away.
Keep people away from and upwind of spill/leak.
Ensure adequate ventilation.
Do not breathe vapours or spray mist.
Do not get in eyes, on skin, or on clothing.
- Environmental precautions : Do not flush into surface water or sanitary sewer system.
Prevent further leakage or spillage if safe to do so.
If the product contaminates rivers and lakes or drains inform respective authorities.
Should not be released into the environment.
- Methods and materials for containment and cleaning up : Ventilate the area.
Dilute with water.
Neutralise with the following product(s):
lime
Contain spillage, soak up with non-combustible absorbent

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

material, (e.g. sand, earth, diatomaceous earth, vermiculite) and transfer to a container for disposal according to local / national regulations (see section 13).
Never neutralise with the following products:
soda ash

SECTION 7. HANDLING AND STORAGE**Handling**

Precautions for safe handling : Handle with extreme care.
Wear personal protective equipment.
Use only in well-ventilated areas.
Use only acid resistant equipment.
Do not breathe vapours or spray mist.
Do not get in eyes, on skin, or on clothing.

Advice on protection against fire and explosion : Normal measures for preventive fire protection.

Storage

Conditions for safe storage, including any incompatibilities : Store in original container.
Keep containers tightly closed in a dry, cool and well-ventilated place.
Storage rooms must be properly ventilated.
Keep in an area equipped with acid resistant flooring.
Store in upright position only.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Protective measures : Ensure that eyewash stations and safety showers are close to the workstation location.
Legal requirements are to be considered in regard of the selection, use and care of personal protective equipment.
Do not breathe vapours or spray mist.
Do not get in eyes, on skin, or on clothing.

Engineering measures : Use with local exhaust ventilation.

Eye protection : Face-shield
Safety goggles

Hand protection : Impervious gloves
Gloves must be inspected prior to use.
Replace when worn.

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

- Skin and body protection : Wear suitable protective equipment.
Wear as appropriate:
acid-resistant protective clothing
- Respiratory protection : In case of insufficient ventilation, wear suitable respiratory equipment.
- Hygiene measures : Separate rooms are required for washing, showering and changing clothes.
Contaminated work clothing should not be allowed out of the workplace.
Keep working clothes separately.
Take off all contaminated clothing immediately.
Remove and wash contaminated clothing before re-use.
Wash hands before breaks and at the end of workday.
Avoid contact with the skin and the eyes.

Exposure Guidelines

| Components | CAS-No. | Value | Control parameters | Update | Basis |
|---------------|-----------|--------------------------------|--------------------|------------|---|
| Sulfuric Acid | 7664-93-9 | TWA : Time weighted average | 1 mg/m3 | 10 2006 | CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) |

| | | | | | |
|---------------|-----------|-------------------------------------|---------|------------|---|
| Sulfuric Acid | 7664-93-9 | STEL : Short term exposure limit | 3 mg/m3 | 10 2006 | CAD AB OEL:Canada. Alberta OELs (Occupational Health & Safety Code, Schedule 1, Table 2) |
|---------------|-----------|-------------------------------------|---------|------------|---|

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

| | | | | | |
|---------------|-----------|--------------------------------|-----------|------------|---|
| Sulfuric Acid | 7664-93-9 | TWA : Time weighted average | 0.2 mg/m3 | 05 2013 | CAD BC OEL:Canada. British Columbia OELs. (Occupational Exposure Limits for Chemical Substances, Occupational Health and Safety Regulation 296/97, as amended) |
|---------------|-----------|--------------------------------|-----------|------------|---|

| | | | | | |
|---------------------|---|-------------------------|--|--|--|
| Further information | : | Form of exposure : Mist | | | |
|---------------------|---|-------------------------|--|--|--|

| | | | | | |
|---------------|-----------|--------------------------------|-----------|------------|---|
| Sulfuric Acid | 7664-93-9 | TWA : Time weighted average | 0.2 mg/m3 | 03 2011 | CAD MB OEL:Canada. Manitoba OELs (Reg. 217/2006, The Workplace Safety And Health Act) |
|---------------|-----------|--------------------------------|-----------|------------|---|

| | | | | | |
|---------------------|---|---------------------------------------|--|--|--|
| Further information | : | Form of exposure : Thoracic fraction. | | | |
|---------------------|---|---------------------------------------|--|--|--|

| | | | | | |
|---------------|-----------|--------------------------------|-----------|------------|---|
| Sulfuric Acid | 7664-93-9 | TWA : Time weighted average | 0.2 mg/m3 | 11 2010 | CAD ON OEL:Canada. Ontario OELs. (Control of Exposure to Biological or Chemical Agents) |
|---------------|-----------|--------------------------------|-----------|------------|---|

| | | | | | |
|---------------------|---|---------------------------------------|--|--|--|
| Further information | : | Form of exposure : Thoracic fraction. | | | |
|---------------------|---|---------------------------------------|--|--|--|

| | | | | | |
|---------------|-----------|---|-----------|------------|---|
| Sulfuric Acid | 7664-93-9 | 8 HR ACL : 8 hour average contamin ation limit: | 0.2 mg/m3 | 05 2009 | CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) |
|---------------|-----------|---|-----------|------------|---|

| | | | | | |
|---------------------|---|---------------------------------------|--|--|--|
| Further information | : | Form of exposure : Thoracic fraction. | | | |
|---------------------|---|---------------------------------------|--|--|--|

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

| | | | | | |
|------------------------|-----------|--|-----------|------------|---|
| Sulfuric Acid | 7664-93-9 | 15 MIN ACL : 15 minute average contamin ation limit: | 0.6 mg/m3 | 05 2009 | CAD SK OEL:Canada. Saskatchewan OELs (Occupational Health and Safety Regulations, 1996, Table 21) |
| Further information | : | Form of exposure : Thoracic fraction. | | | |

| | | | | | |
|---------------|-----------|--------------------------------------|---------|------------|---|
| Sulfuric Acid | 7664-93-9 | TWA : Time weighted average | 1 mg/m3 | 12 2008 | OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) |
|---------------|-----------|--------------------------------------|---------|------------|---|

| | | | | | |
|---------------|-----------|--|---------|------------|---|
| Sulfuric Acid | 7664-93-9 | STEL : Short term exposure limit | 3 mg/m3 | 12 2008 | OEL (QUE):Canada. Quebec OELs. (Ministry of Labor - Regulation Respecting the Quality of the Work Environment) |
|---------------|-----------|--|---------|------------|---|

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

| | | |
|-----------------------------|---|-------------------------|
| Physical state | : | liquid |
| Color | : | colourless |
| Odor | : | odourless |
| pH | : | Note: acidic |
| Melting point/range | : | Note: no data available |
| Boiling point/boiling range | : | Note: no data available |

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

Flash point : Note: Not applicable

Flammability : Not applicable

Lower explosion limit : Note: Not applicable

Upper explosion limit : Note: Not applicable

Density : ca. 1.05 g/cm³ at 20 °C

Water solubility : Note: completely soluble

Partition coefficient: n-octanol/water : Note: no data available

Decomposition temperature : Note: No decomposition if used as directed.

Molecular weight : 98.08 g/mol

Corrosivity : Note: Corrosive to metals

SECTION 10. STABILITY AND REACTIVITY

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous reactions : Hazardous polymerization does not occur.
Gives off hydrogen by reaction with metals.

Conditions to avoid : Protect from heat/overheating.

Incompatible materials : Bases
Reducing agents
Organic materials

F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

Copper
Amines
Alcohols
Aldehydes
Cyanides
Sulphides
Nitriles
Gives off hydrogen by reaction with metals.

Hazardous decomposition products : Sulphur oxides

SECTION 11. TOXICOLOGICAL INFORMATION

Acute oral toxicity : Note: no data available

Acute inhalation toxicity : Note: no data available

Acute dermal toxicity : Note: no data available

Skin irritation : Note: Classification based on Annex VI of regulation 1272/2008/EC.

Eye irritation : Note: Classification based on Annex VI of regulation 1272/2008/EC.

Sensitisation : Note: no data available

Genotoxicity in vitro : Note: Not classified due to data which are conclusive although insufficient for classification.

Carcinogenicity
Sulfuric Acid : Note: An increased risk of cancer in humans has been shown in work-place based studies. This hazard is related to exposure to the mist/vapor of the acid and not the acid solution. Please review IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, Occupational Exposures to Mists and Vapours from Strong Inorganic Acids; and Other Industrial Chemicals, Vol. 54, 1992 and IARC Monographs on the Evaluation of Carcinogenic Risks to Humans, A review of human carcinogens: Chemical Agents and Related

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

Occupations, Vol. 100F, 2012.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity effects

Toxicity to fish : Note: no data available

Toxicity to daphnia and other aquatic invertebrates : Note: no data available

Toxicity to algae : Note: no data available

Elimination information (persistence and degradability)

Biodegradability : Note: The methods for determining biodegradability are not applicable to inorganic substances.

Further information on ecology

Additional ecological information : Neutralisation will reduce ecotoxic effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods : Observe all Federal, State, and Local Environmental regulations.

SECTION 14. TRANSPORT INFORMATION

| | | |
|------------|----------------------|--|
| TDG | UN/ID No. | : UN 3264 |
| | Proper shipping name | : CORROSIVE LIQUID, ACIDIC, INORGANIC, N.O.S. (SULPHURIC ACID) |
| | Class | 8 |
| | Packing group | III |
| | Hazard Labels | 8 |

| | | |
|-------------|-----------|-----------|
| IATA | UN/ID No. | : UN 3264 |
|-------------|-----------|-----------|

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

Description of the goods : CORROSIVE LIQUID, ACIDIC, INORGANIC,
N.O.S.
(Sulphuric acid)

Class : 8

Packaging group : III

Hazard Labels : 8

Packing instruction (cargo aircraft) : 856

Packing instruction (passenger aircraft) : 852

Packing instruction (passenger aircraft) : Y841

IMDG UN/ID No. : UN 3264

Description of the goods : CORROSIVE LIQUID, ACIDIC, INORGANIC,
N.O.S.
(SULPHURIC ACID)

Class : 8

Packaging group : III

Hazard Labels : 8

EmS Number : F-A, S-B

Marine pollutant : no

IMDG Code segregation group 1 – ACIDS,

SECTION 15. REGULATORY INFORMATION

Inventories

US. Toxic Substances Control Act : On TSCA Inventory

Australia. Industrial Chemical (Notification and Assessment) Act : On the inventory, or in compliance with the inventory

Canada. Canadian Environmental Protection Act (CEPA). Domestic Substances List (DSL) : All components of this product are on the Canadian DSL

Japan. Kashin-Hou Law List : On the inventory, or in compliance with the inventory

Korea. Existing Chemicals Inventory (KECI) : On the inventory, or in compliance with the inventory

Philippines. The Toxic Substances and Hazardous : On the inventory, or in compliance with the inventory

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

and Nuclear Waste Control Act

China. Inventory of Existing Chemical Substances : On the inventory, or in compliance with the inventory

New Zealand. Inventory of Chemicals (NZIoC), as published by ERMA New Zealand : On the inventory, or in compliance with the inventory

National regulatory information

US. EPA Emergency Planning and Community Right-To-Know Act (EPCRA) SARA Title III Section 302 Extremely Hazardous Substance (40 CFR 355, Appendix A) : The following component(s) of this product is/are subject to release reporting under 40 CFR 302 when release exceeds the Reportable Quantity (RQ):
Reportable quantity: 1000 lbs

: Sulfuric Acid 7664-93-9

WHMIS Components

: Sulfuric Acid 7664-93-9

NPRI Components

: Sulfuric Acid 7664-93-9

SECTION 16. OTHER INFORMATION

| | HMIS III | NFPA |
|-----------------|----------|------|
| Health hazard | : 3 | 3 |
| Flammability | : 0 | 0 |
| Physical Hazard | : 0 | |
| Instability | : | 0 |

Hazard rating and rating systems (e.g. HMIS® III, NFPA): This information is intended solely for the use of individuals trained in the particular system.

Further information

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a

SAFETY DATA SHEET



F35276 Sulfuric acid 1M 1,00LPE

000000021291

Version 1.2

Revision Date 10/17/2017

Print Date 08/13/2018

guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Final determination of suitability of any material is the sole responsibility of the user. This information should not constitute a guarantee for any specific product properties.

Changes since the last version are highlighted in the margin. This version replaces all previous versions.

Previous Issue Date: 05/30/2017

Prepared by Honeywell Performance Materials and Technologies Product Stewardship Group