

SAFETY DATA SHEET

Creation Date 19-November-2009

Revision Date 19-January-2018

Revision Number 4

1. Identification

Product Name Petroleum ether, boiling range 60-95°C

Cat No. : AC235070000; AC235070010; AC235070025

CAS-No 64742-49-0
Synonyms Ligroïne

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Manufacturer

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 2
Skin Corrosion/Irritation	Category 2
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Respiratory system, Central nervous system (CNS).	
Aspiration Toxicity	Category 1

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor
May be fatal if swallowed and enters airways
Causes skin irritation
Causes serious eye irritation
May cause drowsiness and dizziness

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking

Keep container tightly closed

Ground/bond container and receiving equipment

Use explosion-proof electrical/ventilating/lighting/equipment

Use only non-sparking tools

Take precautionary measures against static discharges

Avoid breathing dust/fume/gas/mist/vapors/spray

Wash face, hands and any exposed skin thoroughly after handling

Use only outdoors or in a well-ventilated area

Wear protective gloves/protective clothing/eye protection/face protection

Response

IF SWALLOWED: Immediately call a POISON CENTER/doctor

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower

IF INHALED: Remove person to fresh air and keep comfortable for breathing

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Call a POISON CENTER/ doctor if you feel unwell

Do NOT induce vomiting

Wash contaminated clothing before reuse

In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Disposal

Dispose of contents/container to an approved waste disposal plant

Other Hazards

Toxic to aquatic life with long lasting effects

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Naphtha (petroleum), hydrotreated light	64742-49-0	>95
Hexane	110-54-3	<5
Cyclohexane	110-82-7	<1.5

4. First-aid measures

General Advice

If symptoms persist, call a physician.

Eye Contact

Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.

Skin Contact

Wash off immediately with plenty of water for at least 15 minutes. If skin irritation persists, call a physician.

Inhalation

Move to fresh air. If not breathing, give artificial respiration. Get medical attention if

	symptoms occur. Risk of serious damage to the lungs.
Ingestion	Clean mouth with water and drink afterwards plenty of water. Do not induce vomiting. Call a physician or Poison Control Center immediately. If vomiting occurs naturally, have victim lean forward.
Most important symptoms/effects	None reasonably foreseeable. Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide. Cool closed containers exposed to fire with water spray.
Unsuitable Extinguishing Media	Do not use a solid water stream as it may scatter and spread fire
Flash Point	-20 °C / -4 °F
Method -	No information available
Autoignition Temperature	258 °C / 496.4 °F
Explosion Limits	
Upper	8.00%
Lower	0.60%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
3	3	0	N/A

6. Accidental release measures

Personal Precautions	Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	Do not flush into surface water or sanitary sewer system.
Methods for Containment and Clean Up	Soak up with inert absorbent material. Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

7. Handling and storage

Handling	Wear personal protective equipment. Ensure adequate ventilation. Avoid ingestion and inhalation. Do not get in eyes, on skin, or on clothing. Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage	Keep containers tightly closed in a dry, cool and well-ventilated place. Flammables area. Keep away from heat and sources of ignition.

8. Exposure controls / personal protection

Exposure Guidelines

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Hexane	TWA: 50 ppm TWA: 176 mg/m ³ Skin	TWA: 20 ppm Skin	TWA: 50 ppm Skin	TWA: 50 ppm TWA: 176 mg/m ³ Skin	TWA: 50 ppm Skin	(Vacated) TWA: 50 ppm (Vacated) TWA: 180 mg/m ³ TWA: 500 ppm TWA: 1800 mg/m ³	IDLH: 1100 ppm TWA: 50 ppm TWA: 180 mg/m ³
Cyclohexane	TWA: 100 ppm TWA: 344 mg/m ³	TWA: 100 ppm	TWA: 100 ppm	TWA: 300 ppm TWA: 1030 mg/m ³	TWA: 100 ppm	(Vacated) TWA: 300 ppm (Vacated) TWA: 1050 mg/m ³ TWA: 300 ppm TWA: 1050 mg/m ³	IDLH: 1300 ppm TWA: 300 ppm TWA: 1050 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Use only under a chemical fume hood. Ensure that eyewash stations and safety showers are close to the workstation location. Use explosion-proof electrical/ventilating/lighting/equipment. Ensure adequate ventilation, especially in confined areas. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection

Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.

Hand Protection

Wear appropriate protective gloves and clothing to prevent skin exposure.

Glove material	Breakthrough time	Glove thickness	Glove comments
Nitrile rubber Viton (R)	See manufacturers recommendations	-	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Follow the OSHA respirator regulations found in 29 CFR 1910.134 or European Standard EN 149. Use a NIOSH/MSHA or European Standard EN 149 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced.

To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained properly

Recommended Filter type: low boiling organic solvent Type AX Brown conforming to EN371

When RPE is used a face piece Fit Test should be conducted

Environmental exposure controls

Prevent product from entering drains. Do not allow material to contaminate ground water system.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	Petroleum distillates
Odor Threshold	No information available
pH	No information available
Melting Point/Range	-40 °C / -40 °F
Boiling Point/Range	60 - 100 °C / 140 - 212 °F @ 760 mmHg
Flash Point	-20 °C / -4 °F
Evaporation Rate	No information available
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	8.00%
Lower	0.60%
Vapor Pressure	105 mmHg @ 20°C
Vapor Density	No information available
Specific Gravity	0.700
Solubility	Insoluble in water
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	258 °C / 496.4 °F
Decomposition Temperature	No information available
Viscosity	0.57 cSt @ 25°C

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Incompatible products. Excess heat. Keep away from open flames, hot surfaces and sources of ignition.
Incompatible Materials	Strong oxidizing agents
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Naphtha (petroleum), hydrotreated light	LD50 > 5000 mg/kg (Rat)	LD50 > 3160 mg/kg (Rabbit)	LC50 = 73680 ppm (Rat) 4 h
Hexane	LD50 = 25 g/kg (Rat)	LD50 = 3000 mg/kg (Rabbit)	LC50 = 48000 ppm (Rat) 4 h
Cyclohexane	> 5000 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	LC50 = 13.9 mg/L (Rat) 4 h

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation Irritating to eyes, respiratory system and skin Vapors may cause drowsiness and dizziness

Sensitization No information available

Carcinogenicity The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Naphtha (petroleum), hydrotreated light	64742-49-0	Not listed	Not listed	Not listed	Not listed	Not listed
Hexane	110-54-3	Not listed	Not listed	Not listed	Not listed	Not listed
Cyclohexane	110-82-7	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Respiratory system Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects The toxicological properties have not been fully investigated.

12. Ecological information

Ecotoxicity

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment. The product contains following substances which are hazardous for the environment.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Naphtha (petroleum), hydrotreated light	Not listed	Not listed	Not listed	LC50: = 2.6 mg/L, 96h (Chaetogammarus marinus)
Hexane	Not listed	LC50: 2.1 - 2.98 mg/L, 96h flow-through (Pimephales promelas)	Not listed	EC50: 3.87 mg/L/48h
Cyclohexane	EC50 >500 mg/L/72h	LC50: 48.87 - 68.76 mg/L, 96h static (Poecilia reticulata) LC50: 24.99 - 44.69 mg/L, 96h static (Lepomis macrochirus) LC50: 23.03 - 42.07 mg/L, 96h static (Pimephales promelas) LC50: 3.96 - 5.18 mg/L, 96h flow-through (Pimephales promelas)	EC50 = 85.5 mg/L 5 min EC50 = 93 mg/L 10 min	EC50 = 0.9 mg/l/48h

Persistence and Degradability Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility Will likely be mobile in the environment due to its volatility.

Component	log Pow
Hexane	4.11
Cyclohexane	3.44

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

Component	RCRA - U Series Wastes	RCRA - P Series Wastes
Cyclohexane - 110-82-7	U056	-

14. Transport information

DOT

UN-No UN3295
Proper Shipping Name HYDROCARBONS, LIQUID, N.O.S.
Hazard Class 3
Packing Group II

TDG

UN-No UN3295
Proper Shipping Name HYDROCARBONS, LIQUID, N.O.S.
Hazard Class 3
Packing Group II

IATA

UN-No UN3295
Proper Shipping Name HYDROCARBONS, LIQUID, N.O.S.
Hazard Class 3
Packing Group II

IMDG/IMO

UN-No UN3295
Proper Shipping Name HYDROCARBONS, LIQUID, N.O.S.
Hazard Class 3
Packing Group II

15. Regulatory information

All of the components in the product are on the following Inventory lists: X = listed

International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Naphtha (petroleum), hydrotreated light	X	-	X	265-151-9	-		X	-	X	X	X
Hexane	X	-	X	203-777-6	438-390-3		X	X	X	X	X
Cyclohexane	X	-	X	203-806-2	-		X	X	X	X	X

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

Component	Canada - National Pollutant Release Inventory (NPRI)	Canadian Environmental Protection Agency (CEPA) - List of Toxic Substances	Canada's Chemicals Management Plan (CEPA)
Hexane	Part 1, Group A Substance Part 5, Individual Substances		Subject to Monitoring and Surveillance Activities
Cyclohexane	Part 1, Group A Substance		

Legend NPRI - National Pollutant Release Inventory

16. Other information

Prepared By Regulatory Affairs
Thermo Fisher Scientific
Email: EMSDS.RA@thermofisher.com

Creation Date 19-November-2009
Revision Date 19-January-2018
Print Date 19-January-2018
Revision Summary This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS