

SAFETY DATA SHEET

Creation Date 22-October-2010

Revision Date 19-January-2018

Revision Number 4

1. Identification

Product Name Isobutyl acetate

Cat No. : AC259830000; AC259830010; AC259830025; AC259830250

CAS-No 110-19-0
Synonyms 2-Methylpropyl acetate

Recommended Use Laboratory chemicals.
Uses advised against Not for food, drug, pesticide or biocidal product use

Details of the supplier of the safety data sheet

Company

Importer/Distributor

Fisher Scientific
112 Colonnade Road,
Ottawa, ON K2E 7L6,
Canada
Tel: 1-800-234-7437

Acros Organics
One Reagent Lane
Fair Lawn, NJ 07410

Manufacturer

Fisher Scientific
One Reagent Lane
Fair Lawn, NJ 07410
Tel: (201) 796-7100

Emergency Telephone Number

For information **US** call: 001-800-ACROS-01 / **Europe** call: +32 14 57 52 11

Emergency Number **US**:001-201-796-7100 / **Europe**: +32 14 57 52 99

CHEMTREC Tel. No.**US**:001-800-424-9300 / **Europe**:001-703-527-3887

2. Hazard(s) identification

Classification

WHMIS 2015 Classification

Classified as hazardous under the Hazardous Products Regulations (SOR/2015-17)

Flammable liquids	Category 2
Specific target organ toxicity (single exposure)	Category 3
Target Organs - Central nervous system (CNS).	
Health Hazards Not Otherwise Classified	Category 1
Prolonged or repeated contact may dry skin and cause irritation or cracking	

Label Elements

Signal Word

Danger

Hazard Statements

Highly flammable liquid and vapor

May cause drowsiness and dizziness

Prolonged or repeated contact may dry skin and cause irritation or cracking

**Precautionary Statements****Prevention**

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking
 Keep container tightly closed
 Ground/bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting/equipment
 Use only non-sparking tools
 Take precautionary measures against static discharges
 Avoid breathing dust/fume/gas/mist/vapors/spray
 Use only outdoors or in a well-ventilated area
 Wear protective gloves/protective clothing/eye protection/face protection

Response

IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower
 IF INHALED: Remove person to fresh air and keep comfortable for breathing
 Call a POISON CENTER/ doctor if you feel unwell
 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish

Storage

Store in a well-ventilated place. Keep container tightly closed
 Store locked up

Disposal

Dispose of contents/container to an approved waste disposal plant

3. Composition/Information on Ingredients

Component	CAS-No	Weight %
Isobutyl acetate	110-19-0	>95

4. First-aid measures

Eye Contact	Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Get medical attention.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Obtain medical attention.
Inhalation	Remove from exposure, lie down. Move to fresh air. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Obtain medical attention.
Ingestion	Clean mouth with water. Get medical attention.
Most important symptoms/effects	Breathing difficulties. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically

5. Fire-fighting measures

Suitable Extinguishing Media	Water spray. Carbon dioxide (CO ₂). Dry chemical. Chemical foam. Cool closed containers exposed to fire with water spray.
-------------------------------------	---

Unsuitable Extinguishing Media	No information available
Flash Point	18 °C / 64.4 °F
Method -	Abel-Pensky (DIN 51755)
Autoignition Temperature	405 °C / 761 °F
Explosion Limits	
Upper	10.5%
Lower	2.4%
Sensitivity to Mechanical Impact	No information available
Sensitivity to Static Discharge	No information available

Specific Hazards Arising from the Chemical

Flammable. Vapors may form explosive mixtures with air. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Hazardous Combustion Products

Carbon monoxide (CO) Carbon dioxide (CO₂)

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

NFPA

Health	Flammability	Instability	Physical hazards
2	3	0	N/A

6. Accidental release measures

Personal Precautions	Remove all sources of ignition. Take precautionary measures against static discharges.
Environmental Precautions	See Section 12 for additional ecological information.

Methods for Containment and Clean Up	Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment. Do not let this chemical enter the environment.
---	---

7. Handling and storage

Handling	Avoid contact with skin and eyes. Avoid contact with clothing. Avoid breathing vapors or mists. Do not ingest. Use explosion-proof equipment. Use only non-sparking tools. Keep away from open flames, hot surfaces and sources of ignition. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.
Storage	Keep in a dry, cool and well-ventilated place. Keep container tightly closed. Keep away from heat and sources of ignition. Flammables area. Keep container tightly closed in a dry and well-ventilated place.

8. Exposure controls / personal protection**Exposure Guidelines**

Component	Alberta	British Columbia	Ontario TWAEV	Quebec	ACGIH TLV	OSHA PEL	NIOSH IDLH
Isobutyl acetate	TWA: 150 ppm TWA: 713 mg/m ³	TWA: 150 ppm	TWA: 150 ppm	TWA: 150 ppm TWA: 713 mg/m ³	TWA: 50 ppm STEL: 150 ppm	(Vacated) TWA: 150 ppm (Vacated) TWA: 700 mg/m ³ TWA: 150 ppm TWA: 700 mg/m ³	IDLH: 1300 ppm TWA: 150 ppm TWA: 700 mg/m ³

Legend

ACGIH - American Conference of Governmental Industrial Hygienists

OSHA - Occupational Safety and Health Administration

NIOSH IDLH: The National Institute for Occupational Safety and Health Immediately Dangerous to Life or Health

Engineering Measures

Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment

Eye Protection	Wear appropriate protective eyeglasses or chemical safety goggles as described by OSHA's eye and face protection regulations in 29 CFR 1910.133 or European Standard EN166.
Hand Protection	Protective gloves

Glove material	Breakthrough time	Glove thickness	Glove comments
Laminated film (Barrier)	> 480 minutes	0.5 mm	Splash protection only

Inspect gloves before use. observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information) gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion. gloves with care avoiding skin contamination.

Respiratory Protection

No protective equipment is needed under normal use conditions.

Recommended Filter type: Organic gases and vapours filter Type A Brown conforming to EN14387

Environmental exposure controls

No information available.

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice. Keep away from food, drink and animal feeding stuffs. Do not eat, drink or smoke when using this product. Remove and wash contaminated clothing before re-use. Wash hands before breaks and at the end of workday.

9. Physical and chemical properties

Physical State	Liquid
Appearance	Colorless
Odor	sweet
Odor Threshold	4.05 ppm
pH	5.0 4g/lH ₂ O
Melting Point/Range	-99 °C / -146.2 °F
Boiling Point/Range	116 - 118 °C / 240.8 - 243.5 °F @ 760 mmHg
Flash Point	18 °C / 64.4 °F
Method -	Abel-Pensky (DIN 51755)
Evaporation Rate	1.5
Flammability (solid,gas)	Not applicable
Flammability or explosive limits	
Upper	10.5%
Lower	2.4%
Vapor Pressure	15 mmHg @ 20 °C
Vapor Density	4.0
Specific Gravity	0.873

Solubility	7 g/L (20°C)
Partition coefficient; n-octanol/water	No data available
Autoignition Temperature	405 °C / 761 °F
Decomposition Temperature	No information available
Viscosity	0.7 mPa s at 20 °C
Molecular Formula	C6 H12 O2
Molecular Weight	116.16

10. Stability and reactivity

Reactive Hazard	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition. Incompatible products. Exposure to moist air or water.
Incompatible Materials	Strong oxidizing agents, Strong bases
Hazardous Decomposition Products	Carbon monoxide (CO), Carbon dioxide (CO ₂)
Hazardous Polymerization	Hazardous polymerization does not occur.
Hazardous Reactions	None under normal processing.

11. Toxicological information

Acute Toxicity

Product Information No acute toxicity information is available for this product

Component Information

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isobutyl acetate	LD50 = 15400 mg/kg (Rat)	LD50 > 17400 mg/kg (Rabbit)	LC0 = 23.4 mg/l (rat; 4 h)

Toxicologically Synergistic Products No information available

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Irritation	No information available
Sensitization	No information available
Carcinogenicity	The table below indicates whether each agency has listed any ingredient as a carcinogen.

Component	CAS-No	IARC	NTP	ACGIH	OSHA	Mexico
Isobutyl acetate	110-19-0	Not listed	Not listed	Not listed	Not listed	Not listed

Mutagenic Effects No information available

Reproductive Effects No information available.

Developmental Effects No information available.

Teratogenicity No information available.

STOT - single exposure Central nervous system (CNS)

STOT - repeated exposure None known

Aspiration hazard No information available

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Endocrine Disruptor Information No information available

Other Adverse Effects See actual entry in RTECS for complete information.

12. Ecological information

Ecotoxicity

Do not empty into drains.

Component	Freshwater Algae	Freshwater Fish	Microtox	Water Flea
Isobutyl acetate	EC50: 370 mg/l (Pseudokirchneriella subcapitata (72 h) (OECD Test Guideline 201)	LC50: = 101 mg/L, 48h static (Leuciscus idus melanotus) LC50: 101 - 123 mg/L, 48h flow-through (Leuciscus idus melanotus)	Not listed	EC50: = 168 mg/L, 24h (Daphnia magna)

Persistence and Degradability Soluble in water Persistence is unlikely based on information available.

Bioaccumulation/ Accumulation No information available.

Mobility . Will likely be mobile in the environment due to its water solubility.

Component	log Pow
Isobutyl acetate	1.72

13. Disposal considerations

Waste Disposal Methods Chemical waste generators must determine whether a discarded chemical is classified as a hazardous waste. Chemical waste generators must also consult local, regional, and national hazardous waste regulations to ensure complete and accurate classification.

14. Transport information

DOT

UN-No UN1213
 Proper Shipping Name ISOBUTYL ACETATE
 Hazard Class 3
 Packing Group II

TDG

UN-No UN1213
 Proper Shipping Name ISOBUTYL ACETATE
 Hazard Class 3
 Packing Group II

IATA

UN-No UN1213
 Proper Shipping Name ISOBUTYL ACETATE
 Hazard Class 3
 Packing Group II

IMDG/IMO

UN-No UN1213
 Proper Shipping Name ISOBUTYL ACETATE
 Hazard Class 3
 Packing Group II

15. Regulatory information

International Inventories

Component	DSL	NDSL	TSCA	EINECS	ELINCS	NLP	PICCS	ENCS	AICS	IECSC	KECL
Isobutyl acetate	X	-	X	203-745-1	-		X	X	X	X	X

Canada

SDS in compliance with provisions of information as set out in Canadian Standard - Part 4, Schedule 1 and 2 of the Hazardous Products Regulations (HPR) and meets the requirements of the HPR (Paragraph 13(1)(a) of the Hazardous Products Act (HPA)).

16. Other information

Prepared By	Regulatory Affairs Thermo Fisher Scientific Email: EMSDS.RA@thermofisher.com
Creation Date	22-October-2010
Revision Date	19-January-2018
Print Date	19-January-2018
Revision Summary	This document has been updated to comply with the requirements of WHMIS 2015 to align with the Globally Harmonised System (GHS) for the Classification and Labelling of Chemicals.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of SDS